

## Elcometer 3508 & 3560 applicator met 4 openingen en reservoir

These film applicators are precision engineered from hardened stainless steel to provide four film thicknesses in one gauge. Simply rotate the applicator to the required thickness, fill the reservoir with the test coating and draw down a uniform stripe.

The Elcometer 3508 is supplied with two reservoirs, ideal for preparing samples for the Elcometer 1720 Abrasion and Washability Testers or for comparing two coatings simultaneously.



**NORMEN:**

ASTM D 823-E (Elcometer 3560)

Technische specificaties

C

Artikelnummer		Model	Filmdikte		Filmbreedte <sup>+</sup>		Certificaat
Metrisch	Engelse maat		µm	mils	mm	inch	
K0003560M201	K0US3560M201	Elcometer 3560/1	30, 60, 90, 120	1, 2, 3, 4	60	2	○
K0003560M202	K0US3560M202	Elcometer 3560/2	50, 100, 150, 200	2, 4, 6, 8	60	2	○
K0003508M001	K0US3508M001	Elcometer 3508/1	100, 150, 200, 250	4, 6, 8, 10	2 x 50	2 x 2	○

<sup>+</sup> Elcometer 3560 totale breedte: 90mm; Elcometer 3508 totale breedte: 165mm

○ Kalibratiecertificaat optioneel leverbaar.