

## **Introducing the Elcometer 480 Single, Dual & Triple Angle Glossmeters**

**Memory:** Store 40,000 date and time stamped readings in up to 2,500 alpha numeric batches.

**USB & Bluetooth Data Output:** Transfer readings to PC, iPhone or Android mobile devices via USB or Bluetooth, for instant reporting using ElcoMaster software.

**Wrist Harness Point:** Prevent gauge damage.

**Battery Door Release:** Two AA batteries provide over 50,000 readings. Rechargeable batteries can also be used.

**Menu Soft Keys:** Intuitive soft-key navigation menus, in over 30 languages.

**Integrated Calibration Tile:** Each gloss tile comes with automatic tile recognition (RFID) for automatic calibration and gauge diagnostics.

**Scratch and Solvent Resistant Colour Display:** Scratch and solvent resistant colour LCD displays readings and graphs.

**Red and Green LED:** Bright dual red and green LED highlights when a reading is within or outside pass / fail limits.

**Ambient Light Sensor:** Internal ambient light detector ensures screen visibility even in bright sunlight.

**Central Measurement Point:** Visible markings on each gauge ensure precise positioning, every time.

**Gauge Optics:** The Elcometer 480 accurately and repeatedly measures 20, 60 & 85° Gloss, % Reflectance and Haze. 3 readings per second for all angles in standard mode. 10 readings per second for all angles in scan mode.

**Calibration Serial Number:** Serial number and gloss values are printed on the rear of the holder – no need to remove the gauge from the tile.

**Robust:** Designed for use in harsh environments.

**The Elcometer 480:** setting the benchmark for hand-held gloss measurement.